

The new control panel CPX200: Low price | Functional | Customize to the customer needs

New project of EBS, which is now in the final stage, involves the creation of
The most customer-friendly control panel:

➤ **INTEGRATED with GSM / GPRS transmitter**

- Signal transmission via GPRS / SMS
 - immediate notification about emergency situations;
- Remote configuration and firmware upgrade
 - comfortable servicing and time savings;
- Encryption of transmitted data using the AES cipher
 - full data transfer safety;
- The signal is sent through OSM.2007. This EBS receiver ensures complete transfer reliability;
- GSM / GPRS connection control
 - automatic retrieving of the connection with the monitoring station.



➤ **INPUTS**

- 6 line-type DEOL, possible conversion on EOL
- Additional input for arming the system by radio line (radio remote controller)

➤ **OUTPUT**

- 1 high-current (0,7A) alarm output
- 2 low-current (50mA)

➤ **SUPERVISED LINES**

- Delayed
- Immediate
- 24 hrs. (Continuous)
- Armed/disarmed

➤ **PROGRAMMABLE SYSTEM TIME** - time for enter / leave / alarm duration

➤ **PROGRAMMING THE CONTROL PANEL SETTINGS**

- LOCAL (the keypad or a computer connected to the RS-232)
- REMOTE (via GPRS, SMS or CSD)

➤ **PROGRAMMING SOCKET** - required cable GD-PROG

➤ **SCREW TERMINAL** - angle rising clamp

➤ **ANTENNA CONNECTION** - SMA, mounted directly on PCB

Control panel has an acoustic signal confirming arming / disarming the system by radio remote controller.

➤ **CODES**

- 1 administrator code (root)
- 1 service code
- 3 user codes

➤ The possibility of limiting the terms of reference for some of the codes

➤ **Autodiagnostic** features for basic components of the system

➤ Opportunity to **review faults**, memory of alarm signals and other events

➤ **The history** of system events evidence up to 5000 events