

Key Features

- UL 521 approved File No S36573
- Detection at any point along the cable
- Low installation and maintenance costs
- Reliable solution for hazardous areas
- 185°C (365°F) Activation temperature



Overview

Proline Digital Linear Heat Detection Cable uses fixed temperature detection technology to provide an easy method for sensing changes in temperature levels. The cable can offer alternative overheat protection in a vast range of applications and environments, from tunnels, cable trays, warehousing to sensing changes in temperature within escalators and other applications where many risks of fire are hidden from view.

The digital linear heat detection cable can be directly connected to a single zone of a conventional fire alarm control panel, or, using an addressable zone/switch monitor, the digital linear heat detection cable can easily be interfaced to an addressable loop.

Digital linear heat detection cable is comprised of a pair of twisted low resistance, tri-metallic conductors, sheathed in advanced temperature sensitive polymers. When the cable reaches the required temperature the two twisted cores will fuse together, with a fire triggering resistor attached to the input interface and a single core of linear heat cable to activate an alarm at the main fire panel.

The High Temperature coated linear heat cable is manufactured from two different types of nylon, with the outer sheath being a chemical resistant material. Commonly used in high temperature areas, hazardous and safe areas where chemicals such as hydrocarbon fuel oils, diesel, kerosene etc. are present.

Technical Data

| | |
|-----------------------------------|---|
| Construction: | Overall insulated, twisted pair of tri-metallic cores |
| Insulation: | 1kV tested protective outer coat |
| Approvals: | CE Marked, RoHS Compliant, UL 521 approved File No S36573 |
| Maximum Zone Length: | 3,000m (10,000ft) |
| Wire Overall Diameter: | 3.60mm ± 0.12mm (0.142" ± 0.005") |
| Minimum bend radius: | 50 mm (2") |
| Ambient Temperature Range: | -40°C to 125°C (-40°F to 257°F) |
| Activation Temperature: | 185°C (365°F) |

Technical Data: Electrical

| | |
|---------------------------------|--------------------------------|
| Max Voltage Rating: | 30Vac, 42Vdc |
| Resistance: | ~100Ω/km (29Ω/kft) per leg |
| Velocity of Propagation: | ~55% |
| Capacitance: | 88 -150 pF/m (26-45 pF/ft) |
| Inductance: | 540-1050 nH/m (165 -320 nH/ft) |

Chemical Resistance Data (other coatings for comparison)

| Chemical | PROLINE NYLON | PROLINE PVC | PROLINE SILICONE |
|-------------------|---------------|-------------|------------------|
| Butane | ●●●● | ●●●● | ●●● |
| Diesel Fuel | ●●●● | ●●●● | ●●● |
| Ethanol | ●●●● | ●●●● | ●●●● |
| Fuel Oils | ●●●● | ●●●● | ●●● |
| Gasoline Unleaded | ●●●● | ●●● | ●●● |
| Jet Fuel | ●●●● | ●●●● | ●●● |
| Kerosene | ●●●● | ●●●● | ●●● |
| Lubricants | ●●●● | ●●●● | ●●● |
| Methanol | ●●●● | ●●●● | ●●●● |
| Natural Gas | ●●●● | ●●●● | ●●●● |
| Sea Water | ●●●● | ●●●● | ●●●● |
| Sodium Peroxide | ●●●● | ●●● | ●● |

Ordering Information

| Part Number | Description |
|-------------|---|
| TH185-100 | Digital LHD Cable, Nylon Red, 185°C Alarm Temp, UL, 100m |
| TH185-200 | Digital LHD Cable, Nylon Red, 185°C Alarm Temp, UL, 200m |
| TH185-500 | Digital LHD Cable, Nylon Red, 185°C Alarm Temp, UL, 500m |
| TH185-1000 | Digital LHD Cable, Nylon Red, 185°C Alarm Temp, UL, 1000m |