

AD105-1000

Alarmline II Digital LHD Cable 105°C (221°F) w/ PVC Sheath - 1000m

General

The AD105-1000 is a Digital Linear Heat Detection (LHD) cable with a 105°C (221°F) fixed temperature activation rating. It has a Standard PVC outer sheath making it suitable for internal applications and is supplied in 1000m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge', 'A', 'P', and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Details

- cUL/UL 521 approved
- FM approved (Class 3210)
- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas
- RoHS Compliant

AD105-1000

Alarmline II Digital LHD Cable 105°C (221°F) w/ PVC Sheath - 1000m

Technical specifications

Electrical

Operating voltage	0 to 30VAC, 0 to 42VDC
-------------------	------------------------

Operating voltage	0 to 30VAC, 0 to 42VDC
-------------------	------------------------

Detection

Alarm temperature (typical)	+105°C
--------------------------------	--------

Conductor

Resistance	91 Ω/km (27.7 Ω/1000ft.)
------------	--------------------------

Capacitance	< 73 pF/m (<22 pF/ft.)
-------------	------------------------

Inductance	< 1.65 μH/m (<0.5 μH/ft.)
------------	---------------------------

Physical

Net weight	20 kg
------------	-------

Colour	White
--------	-------

Environmental

Relative humidity	0 to 100% noncondensing
-------------------	-------------------------

Environment	Indoor, Outdoor
-------------	-----------------

Protection	PVC Sheath
------------	------------

Ambient temperature (max)	69°C (156°F)
------------------------------	--------------

Relative humidity	0% to 100%
-------------------	------------

Standards & regulation

Certification	CE, FM, UL
---------------	------------

Mechanical

Outside diameter (Nominal)	3.6mm ± 0.12mm
-------------------------------	----------------

No of cores	2
-------------	---

Colour	White
--------	-------

Weight	20kg
--------	------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 11 February 2019 - 19:12



**United
Technologies**

Climate | Controls | Security